

インコネルるつぼ (Straight Wall, Cover)



Inconel alloy 601 has excellent resistance to oxidation in the 1000°C to 1200°C temperature range and also has good corrosion resistance to many acid and aqueous salt solutions. This high resistance to oxidation, carburization or sulfidation makes Inconel alloy 601 well suited for determining moisture, volatiles, fix-carbon and ash in most coal and coke products, or wood pulp or fiber. The alloy is well suited for use with sodium hydroxide solutions and exhibits good resistance to nitric acid and low concentrations of phosphoric acid. It is also unaffected by rapid changes from hot to cold and retains its mechanical strength at elevated temperatures. Strong alkaline or oxidizing fusions are not recommended with Inconel alloy 601.

| INCONEL STRAIGHT WALL | | | | CRUCIBLE | | COVER | | |
|---|-----------------------|-----|-----------------|----------|--------------------------|-------------------|----------------|-------------------|
| CAPACITY ML | OUTSIDE DIA IN. MM | | DEPTH IN. MM | | PART NUMBER | PRICE EA US \$ | PART NUMBER | PRICE EA US \$ |
| 5 | 0.83 | 21 | 0.75 | 19 | 30-0005SW | CALL | 30-0005C | CALL |
| 10 | 1.07 | 27 | 0.87 | 22 | 30-0010SW | CALL | 30-0010C | CALL |
| 15 | 1.32 | 33 | 0.87 | 22 | 30-0015SW | \$38.26 | 30-0015SC | \$13.88 |
| 20 | 1.32 | 33 | 1.14 | 29 | 30-0020SW | \$38.35 | 30-0015SC | \$13.88 |
| 25 | 1.84 | 47 | 0.87 | 22 | 30-0025SW | \$40.36 | 30-0025C | \$14.37 |
| 35 | 1.84 | 47 | 1.14 | 29 | 30-0035SW | \$42.12 | 30-0025C | \$14.37 |
| 45 | 1.84 | 47 | 1.34 | 34 | 30-0045SW | \$44.47 | 30-0025C | \$14.37 |
| 55 | 1.84 | 47 | 1.60 | 41 | 30-0055SW | \$46.79 | 30-0025C | \$14.37 |
| 75 | 2.01 | 51 | 1.61 | 41 | 30-0075SW | \$53.35 | 30-0075C | \$16.42 |
| 100 | 2.34 | 59 | 1.77 | 45 | 30-0100SW | \$63.72 | 30-0100C | \$17.95 |
| 250 | 3.25 | 83 | 2.25 | 57 | 30-0250SW | \$84.97 | 30-0250C | \$23.58 |
| 500 | 4.09 | 104 | 2.49 | 63 | 30-0500SW | \$132.76 | 30-0500C | \$39.01 |
| 1000 | 5.00 | 127 | 3.51 | 89 | 30-1000SW | CALL | 30-1000SC | CALL |
| 1500 | 6.00 | 152 | 3.90 | 99 | 30-1500SW | CALL | 30-1000LC | CALL |
| Above sizes and capacities approximate. | | | | | Standard thickness .040" | | | |

2020年1月ご発注分より適用（ユーザー価格）。

単価は、FOB 価格（オレゴン、アメリカ）で、メーカーより、アナウンスなく変動する可能性があります。

円価格（ユーザー価格）は、US\$ x 為替 x 個数 + 送料となります。表面仕上品 (Acid Etch) は、US\$5/1 部品必要となり、御発注時に明記必要です。

送料の目安は、50 個まで、15,000 円、100 個まで、20,000 円。その他経費として、海外送金手数料が、約 5,000 円かかります。

見積書にて、正式価格はお知らせします。商社様は、担当者まで、ご相談ください。